
Part 23 Policy Update

Flight Test

Presentation to: FTW DER Conference

Name: Peter L. Rouse Date: May 25,2006





Presentation Overview

- Small Jet History / Philosophy
- Small Jet Rulemaking Attempt
- Small Jet Projects
- New Systems Policy



Part 23 Jet History / Philosophy

- Prior to adoption of commuter category
- Early programs adopted pre-amendment 42, part 25 requirements for subpart B and G
- We get better single engine performance and balanced field length in exchange for relaxed flight characteristics
- Since the adoption of the commuter category we have tried to use part 23 to replace the old part 25 requirements so that we can use part 23 flight characteristics

Current Small Jet Approach

- Directorate hosted a flight test meeting back around the turn of the century to discuss future of small part 23 jets
- Conclusion for subpart B and G:
 - Under 6000 pounds = normal category requirements
 - Over 6000 pounds = commuter category
- Rational provided for increased safety:
 - Promoting the small jets over small recips twins
 - Part 23 turbine now requires guaranteed performance
 - Expected new generation of avionics
 - Required training



Rulemaking Efforts – Small Jets

Background

- Order 1110.135 established the Part 135/125 Aviation Rulemaking Committee (ARC)
- The ARC tasked a working group to review part 23 for small jets the group reviewed normal and commuter category rules
- Working group determined that jets under 12,500 lbs use part 23 with typically applied special conditions folded in
- Working group determined jets between 12,500 and 19,000 pounds use commuter category rules







Eclipse

Mustang





Embraer Light Jet (300) and Very Light Jet (100)





- Cabin Mock-up for model 100
- Cabin for 300 includes an additional row of seats

Grob SPn Utility Jet



ATG Javelin



New Policy

2005

- ACE-05-04,1-G Stall Speed
- PS-ANE-2003-35-1-R0, Propeller Ice Protection Equipment

2006

 No new requirements for inflight engine starting for single engine airplanes

New Policy



Compliance with §23.903(f), Restart Envelope, "One way, but not the only way...."

New Environmental Policy - 23.1301-23.1309

The guidance -

- allows the depth of the environmental qualification to be commensurate with the severity of the hazard
- It is based on the five failure condition classifications defined in AC 23.1309-1C ranging from no safety effect to catastrophic
- should reduce the amount of environmental qualification, especially for equipment that has no safety effect and equipment that has only minor failure conditions

High voltage systems (HID Lights, etc) can be a source of EMI and may need to be tested to a higher environmental levels or EMI

New Guidance – GAMA Doc #12

"GAMA Class" cockpit

- Meant to streamline certification
- Establishes a baseline for all new part 23 displays –
 PFD & MFD
- Defines field-of-view for many items
- Leaves creative freedom, but states minimum standard
- Glass to Glass transition easier

Brief Overview of the Topics Addressed in the AC

- Intended Function
- Synthetic Terrain/Vision Imagery
- Terrain Alert System not necessarily TAWS
- Airplane Reference Relative to Terrain
- Heading Integrity
- Horizon Line
- Moving Map that Corresponds to and Compliments the SV PFD Display
- Failure Modes



- Terrain Color and Depiction
- Minimums Audio Callout Capability
- Cultural Features
- Terrain Resolution
- Terrain Database Integrity
- Display Update Rates
- Aircraft Flight Manual Supplement
- Unusual Attitude Recovery

Specific Guidance For Pathway Displays

- Pathway Lateral and Vertical Limits
- Precision Approach Guidance
- Pathways and Terrain

Test and Evaluation Methods and Criteria for Compliance



Approved Synthetic Terrain / Vision

Universal's Vision 1







Approved Synthetic Terrain / Vision

Chelton Flight Systems








Conventional Display



New Version of Conventional Display



Instrument Conditions Outside View



Synthetic Vision Display






Conventional Display



New Version of Conventional Display



Visual Conditions Outside View



Synthetic Vision Display





Simulated CAT III Approach

New Policy - FADEC

- Question: How Do I Install It?
 - The EEC is first certified on the 14 CFR part 33 engine through a Supplemental Type Certificate (STC) or Amended Type Certificate (ATC) process.
 - The EEC is then installed and certified on the 14 CFR part 23 certificated airplane using the Supplemental Type Certificate (STC) or Amended Type Certificate (ATC) process.
- Answer: A Supplemental, Amended, or New Type Certificate (New Aircraft)

Policy – Additional Issues

AC 23.1309-1C Figure 2 Showing Classes of Airplanes:

- Already provided relaxation from the old requirements of AC 23.1309-1B
- Design assurance levels are shown
- Probability values are shown
- The design assurance levels are for software and complex hardware – not for lightning and HIRF

New Technology – Safety is Selling...Finally



Obstacle Databases Are A Good Thing

Things you don't see everyday in aviation...



Ford
"Non-Lifting Body"
Launch Test

And finally, from the "How I Lost My Job" files...



Questions?

